

EXHIBIT A

Thermoplastics - An Introduction

Page 2 of 5

Microsystems and Nanotechnology
MeetingsPolymer Science and Technology -
5 Day Course

Styrene Engineering

Partners
Nanotechnology

Eng-Tips Forum

Medical News

Building/Construction


Polystyrene, Wide Spec
Virgin
www.globaltradinginc.comThermal Conduct.
Plastics
Resource for thermally
conductive
thermoplastics in
electrical parts
www.cncaptch.comChemical Manufacturers
Chemical Petrochemical
B2B Listings
products suppliers
manufactures
sulekhab2b.comBuy Polyethylene Online
Alastian, no-frills quality
PP & PE
See real-time prices.
Register Now!
www.alastian.com**Figure 1** Molecular Arrangement of Polymer
Chains

Table 1 lists a selection of amorphous and semi-crystalline polymers.

Table 1. Amorphous and semi-crystalline
polymers.


Amorphous	Semi-crystalline
Polyamideimide	Polyetheretherketone
Polyethersulphone	Polytetrafluoroethylene
Polyetherimide	Polyamide 6,6
Polyarylate	Polyamide 11
Polysulphone	Polyphenylene sulphide
Polyamide (amorphous)	Polyethylene terephthalate
Polymethylmethacrylate	Polyoxymethylene
Polyvinylchloride	Polypropylene
Acrylonitrile butadiene	High Density
styrene	Polyethylene
Polystyrene	Low Density
	Polyethylene

Amorphous Polymers

Generally, fully amorphous polymers are stiff, brittle and clear in the virgin state. The temperature and stress state have a profound effect on the molecular arrangement and hence the properties of a polymer. Under the action of sufficient stress, the polymer chains can uncoil and align over a period of time. At elevated

temperatures, polymer chains have enough energy to rotate and coil up further.

Figure 2 shows schematically the effect of temperature on the elastic modulus of an amorphous and a semi-crystalline polymer. Below a temperature known as the glass transition temperature, T_g , the structure of amorphous polymers is termed 'glassy', with a random arrangement of the polymer chains, similar to the random molecular arrangement found in glass. As the temperature increases to T_g , the polymer chains have sufficient thermal energy to rotate, resulting in a drop in modulus. One definition of T_g is the temperature at which molecular rotation about single bonds becomes favourable as the temperature increases. At temperatures above T_g but below the melting temperature, T_m , there is a 'rubbery region', where the material can exhibit large elongations under relatively low load. Amorphous thermoplastics are generally used at temperatures below their T_g , where they can be brittle, just like glass. There are, however, certain exceptions. Polycarbonate (PC) is amorphous yet it is considered tough at temperatures well below its T_g . When it does fracture below its T_g , it does so in a brittle manner, but this requires a large amount of energy and so PC is considered tough, finding use in applications requiring impact resistance, e.g. safety helmets and bullet proof glazing. This behaviour is due to the chemical bonds in polycarbonate rather than the arrangement of the polymer chains.



floridanae

Figure 2. The effect of temperature on the Elastic Modulus (assuming both types of polymer have the same Tg and Tm)

Semi-Crystalline Polymers

Semi-crystalline materials such as polyamides do not exhibit a clear Tg or 'rubbery' region, although one is often quoted as the amorphous parts of the structure will undergo some transition. For these polymers the main transition occurs at Tm when the crystalline regions break down (see Fig. 2). Some chain rotation in the amorphous regions will occur below Tm, giving some impact resistance at these temperatures. Values of Tg and Tm for a number of polymers are given in Table 2.

Table 2. Glass transition and melting temperatures for a range of thermoplastics.

Polymer	Tg (°C)	Tm (°C)
High density polyethylene (HDPE)	-	135
Polypropylene (PP)	-10	175
Polystyrene (PS)	100	-
Polymethylmethacrylate (PMMA)	105	-
Polyvinylchloride (PVC)	65	-
Natural rubber (NR)	-75	25
Polydimethyl siloxane (PDMS)	-125	-55
Polyoxymethylene (POM)	125	175
Polycarbonate (PC)	150	-
Polyethylene terephthalate (PET)	70	265
Polyetheretherketone (PEEK)	145	335
Nylon 6 (PA6)	50	215
Polyamideimide (PAI)	295	-
Polysulphone (PSU)	195	-
Polyphenylene sulphide (PPS)	90	285
Polyethersulphone (PES)	230	-
Polyetherimide (PEI)	218	-
Polytetrafluoroethylene (PTFE)	20	325
Liquid crystal polymer (LCP)	-	420

Table 2. Values of Tg and Tm for selected polymers

Abstracted From the Materials Information Service, edited by Justin Furness

For more information on Materials Information Service please visit The Institute of Materials.

DEC-22-2005 THU 06:44 PM WORKMAN NYDEGGER



FAX NO. 8013281707

P. 27

Thermoplastics - An Introduction

Page 5 of 5

top

◀  

AZoM™ - Metals, Ceramics, Polymers, Composites, An Engineers Resource...AZoM™.com Pty.Ltd Copyright © 2000-2005

<http://www.azom.com/details.cfm?ArticleID=83&head=Thermoplastics%2B-%2BAn%2BR> 12/7/2005
PAGE 27/32 * RCVD AT 12/22/2005 8:35:34 PM [Eastern Standard Time] * SVR:USPTO-EFXRF-6/26 * DNIS:2738300 * CSID:8013281707 * DURATION (mm:ss):12-20

BEST AVAILABLE COPY